

## LISTING OF CLAIMS

1. (Cancelled)
2. (Cancelled)
3. (Cancelled)
4. (Cancelled)
5. (Cancelled)
6. (Cancelled)
7. (Cancelled)
8. (Cancelled)
9. (Cancelled)
10. (Cancelled)
11. (Cancelled)
12. (Cancelled)
13. (Cancelled)
14. (Cancelled)
15. (Cancelled)
16. (Cancelled)
17. (Cancelled)
18. (Cancelled)
19. (Cancelled)
20. (Cancelled)
21. (Cancelled)
22. (Cancelled)
23. (Cancelled)

24. (Cancelled)
25. (Cancelled)
26. (Cancelled)
27. (Cancelled)
28. (Cancelled)
29. (Cancelled)
30. (Cancelled)
31. (Cancelled)
32. (Cancelled)
33. (Cancelled)
34. (Cancelled)
35. (Cancelled)
36. (Cancelled)
37. (Cancelled)
38. (Cancelled)
39. (Cancelled)
40. (Cancelled)
41. (Cancelled)
42. (Cancelled)
43. (Cancelled)
44. (Cancelled)
45. (Cancelled)
46. (Cancelled)
47. (Cancelled)
48. (Cancelled)

49. (Currently Amended) An ink-jet recording process, comprising the step of ejecting the ink from an orifice in response to recording signals, ~~said ink comprising~~ wherein said ink shows fluorescence intensity by ultraviolet light, and wherein said ink comprises:

(i) first and second organic compounds which are incompatible with each other;

(ii) at least one of a compound exhibiting fluorescence properties and a coloring material exhibiting fluorescence properties; and

(iii) a liquid medium dissolving or dispersing the components (i) and (ii) therein.

50. (Original) The ink-jet recording process according to Claim 49, wherein the step comprises a sub-step of applying thermal energy to the ink to eject the ink from an orifice.

51. (Original) A recorded article obtained by the ink-jet recording process according to Claim 50, wherein the fluorescence intensity of a recorded portion formed on wood-free paper has a proportional relationship to the water content in the wood-free paper.

52. (Original) The recorded article according to Claim 51, which has a maximum wavelength for excitation and a fluorescence maximum wavelength, and the maximum wavelength for excitation is shorter than the fluorescence maximum wavelength.

53. (Original) A recorded article having a colored portion exhibiting fluorescence on a recording medium, wherein the colored portion contains at least one of a compound exhibiting fluorescence and a coloring material exhibiting fluorescence and has an interface at which incident light on the colored portion is reflected, the interface being between the outermost surface thereof and the surface of the recording medium.

54. (Currently Amended) A recording unit comprising an ink container containing ink and a head portion for ejecting the ink, wherein said ink shows fluorescence intensity by ultraviolet light, ~~said ink container containing~~ ink comprising:

(i) first and second organic compounds which are incompatible with each other;

(ii) at least one of a compound exhibiting fluorescence properties and a coloring material exhibiting fluorescence properties; and

(iii) a liquid medium dissolving or dispersing the components (i) and (ii) therein.

55. (Original) The recording unit according to Claim 54, wherein the head portion has a construction that thermal energy is applied to the ink to eject the ink.

56. (Original) The recording unit according to Claim 54, wherein the ink container comprises a polyolefin.

57. (Original) The recording unit according to Claim 54, wherein the ink container has an ink holding member therein.

58. (Original) The recording unit according to Claim 57, wherein the ink holding member comprises at least one selected from the group consisting of polyurethane, cellulose, polyvinyl acetate and polyolefin.

59. (Original) The recording unit according to Claim 57, wherein the ink holding member comprises a polymer formed by a condensation or polymerization reaction of organic compound(s).

60. (Original) The recording unit according to Claim 57, wherein the ink holding member comprises a porous material.

61. (Original) The recording unit according to Claim 60, wherein the ink holding member has a surface being in contact with the ink container.

62. (Original) The recording unit according to Claim 57, wherein the ink holding member has a multi-layer structure.

63. (Original) The recording unit according to Claim 62, wherein the direction of the multi-layer arrangement of the multi-layer structure is aligned in an ink discharging direction of the ink container.

64. (Original) The recording unit according to Claim 62, wherein the ink holding member has a contact surface with the ink container.

65. (Original) The recording unit according to Claim 57, wherein the ink holding member is composed of fiber flocculate.

66. (Original) The recording unit according to Claim 65, wherein the fiber flocculate is aligned in an ink discharging direction of the ink container.

67. (Original) The recording unit according to Claim 66, wherein the ink holding member has a contact surface with the ink container.

68. (Currently Amended) An ink cartridge comprising an ink container containing ink, wherein said ink shows fluorescence intensity by ultraviolet light, said ink comprising:

(i) first and second organic compounds which are incompatible with each other;

(ii) at least one of a compound exhibiting fluorescence properties and a coloring material exhibiting fluorescence properties; and

(iii) a liquid medium dissolving or dispersing the components (i) and (ii) therein.

69. (Original) The ink cartridge according to Claim 68, wherein the ink container comprises a polyolefin.

70. (Original) The ink cartridge according to Claim 68, wherein the ink container has an ink holding member therein.

71. (Original) The ink cartridge according to Claim 70, wherein the ink holding member comprises at least one selected from the group consisting of polyurethane, cellulose, polyvinyl acetate and polyolefin.

72. (Original) The ink cartridge according to Claim 70, wherein the ink holding member is composed of a polymer formed by a condensation or polymerization reaction of organic compound(s).

73. (Original) The ink cartridge according to Claim 70, wherein the ink holding member has a porous structure.

74. (Original) The ink cartridge according to Claim 73, wherein the ink holding member has a contact surface with the ink container.

75. (Original) The ink cartridge according to Claim 70, wherein the ink holding member has a multi-layer structure.

76. (Original) The ink cartridge according to Claim 75, wherein the direction of the multi-layer arrangement of the multi-layer structure is aligned in an ink discharging direction of the ink container.

77. (Original) The ink cartridge according to Claim 76, wherein the ink holding member has a contact surface with the ink container.

78. (Original) The ink cartridge according to Claim 70, wherein the ink holding member is composed of fiber flocculate.

79. (Original) The ink cartridge according to Claim 78, wherein the fiber flocculate is aligned in an ink discharging direction of the ink container.

80. (Original) The ink cartridge according to Claim 79, wherein the ink holding member has a contact surface with the ink container.

81. (Currently Amended) An ink-jet recording apparatus comprising an ink container containing ink and a head portion for ejecting the ink, wherein said ink shows fluorescence intensity by ultraviolet light, said ink comprising:

(i) first and second organic compounds which are incompatible with each other;

(ii) at least one of a compound exhibiting fluorescence properties and a coloring material exhibiting fluorescence properties; and

(iii) a liquid medium dissolving or dispersing the components (i) and (ii) therein.

82. (Currently Amended) A method of enhancing fluorescence of a fluorescent colored portion of a recorded article comprising a recording medium and the colored portion provided thereon, wherein the colored portion is formed by an ink-jet recording process comprising the step of applying an ink to a recording medium by an ink-jet system, wherein said ink shows fluorescence intensity by ultraviolet light, and an ink comprising



(i) first and second organic compounds which are incompatible with each other;

(ii) at least one of a compound exhibiting fluorescence and a coloring material exhibiting fluorescence; and

(iii) a liquid medium dissolving or dispersing the components (i) and (ii) therein is used as said ink.

83. (Original) A method of enhancing fluorescence of a fluorescent colored portion of a recorded article comprising a recording medium and the colored portion provided thereon, which comprises providing a reflecting interface for incident light on the colored portion from the outside between the outermost surface of the colored portion and the surface of the recording medium at the colored portion.

84. (Currently Amended) A method of elongating the life time of fluorescence of a fluorescent colored portion of a recorded article comprising a recording medium and the colored portion provided thereon, wherein the colored portion is formed by an ink-jet recording process comprising the step of applying an ink to a recording medium by an ink-jet system, wherein said ink shows fluorescence intensity by ultraviolet light, and an ink comprising

(i) first and second organic compounds which are incompatible with each other;

(ii) a compound having a vapor pressure not lower than that of diethyleneglycol ;

(iii) at least one of a compound exhibiting fluorescence properties and a coloring material exhibiting fluorescence properties; and

(iv) a liquid medium dissolving or dispersing the components (i), (ii) and (iii) therein is used as said ink.

85. (New) The ink-jet recording process according to Claim 49, wherein the coloring material is C.I. Acid Red 52, and the content of the coloring material is at most 0.4% by weight based on the total weight of the ink.

86. (New) The ink-jet recording process according to Claim 54, wherein the coloring material is C.I. Acid Red 52, and the content of the coloring material is at most 0.4% by weight based on the total weight of the ink.

87. (New) The ink-jet recording process according to Claim 68, wherein the coloring material is C.I. Acid Red 52, and the content of the coloring material is at most 0.4% by weight based on the total weight of the ink.

Applicants' undersigned attorney may be reached in our Costa Mesa office by telephone at (714) 540-8700. All correspondence should continue to be directed to our address given below.

Respectfully submitted,

A handwritten signature in black ink, appearing to read "Michael K. O'Neill", is written over a horizontal line.

Attorney for Applicants  
Michael K. O'Neill  
Registration No. 32,622

FITZPATRICK, CELLA, HARPER & SCINTO  
30 Rockefeller Plaza  
New York, New York 10112-3801  
Facsimile: (212) 218-2200

CA\_MAIN 90309v1